AMPROBE®

Data Sheet

TMD-53

Thermocouple Thermometer K/J

Amprobe TMD-53 series of thermometers is a professional choice for HVAC/R technicians, electricians, research, industrial process, and quality control. The dual inputs allow easy super-heat and sub-cool temperature measurement as well as cut-out and in temperature measurements.

- **K/J-type thermocouple selection**
- **Dual input**
- **MAX/MIN with elapsed time, AVG, REL, HOLD functions**
- **TIME setting, REL setting**
- **Warning beeper with Hi/Lo setting**
- **Resolution 0.1°C to 0.2°F**
- **User selectable °C/°F**

No hassle warranty

No waiting.

No shipping charges.

Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: $500 MSLP limit)

Distributed by:

TESTERS AND TOOLS.COM
Trust Experience Reliability
sales@testersandtools.com
Tel: 602-795-4033, Fax: 602-795-4624

N10140

TMD-53 Thermocouple Thermometer K/J

Data Sheet

General Specifications

Display	5 digit liquid crystal display (LCD)
Polarity	Automatic, positive implied, negative polarity indication.
Low Battery Indication	The "⊟" is displayed when the battery voltage drops below the operating level.
Auto Power Off	30 minutes
Measurement Rate	One time/second.
Operating Environment	0°C to 50°C (32°F to 122°F) <80% R.H.
Storage Environment	-20°C to 60°C (-4°F to 140°F) <70% R.H. with battery removed from meter.
Accuracy	Stated accuracy at 23°C ±5°C, <75% R.H.
Battery	1.5V x 4pcs AAA size
Battery Life	200 hours typical
Dimensions	L241.3 X W157.98 XH76.2mm (9.5 X 6.22 X3 in)
Weight	Approx. 286g (0.63 lb) including batteries and packaging box.

Electrical Specification

Feature	**Range**
Thermocouple Type	K/J
Temperature	K-TYPE: -200°C-1370°.C, -328°F-2498°F J-TYPE: -200°C-1050°.C, -328°F-1922°F
Accuracy	±(0.05%rdg + 0.3°C) on -50°C to 1370°C ±(0.05%rdg + 0.7°C) on -50°C to -200°C ±(0.05%rdg + 0.6°F) on -58°F to 2498°F ±(0.05%rdg + 1.4°F) on -58°F to -328°F
Number Of Parameters On The Display	3
Included Accessories	Users Manual, K type thermocouple (2) Batteries (4)

Amprobe® Test Tools
website: www.Amprobe.com
email: info@amprobe.com
Everett, WA 98203
Tel: 877-AMPROBE

Amprobe® Test Tools Europe
In den Engematten 14
79286 Glottertal, Germany
Tel.: +49 (0) 7684 8009 - 0

Distributed by:
TESTERS AND TOOLS.COM
Trust Experience Reliability
sales@testersandtools.com
Tel: 602-795-4033, Fax: 602-795-4624

©2010 Amprobe Test Tools. All rights reserved.

6/2010 TMD-53_DS Rev A