


Dial Stem Thermometers

 **Choice of Flat Surface or Penetration Stem Thermometer**
For use in liquids, semi-solids and solids

Features:

- **Flat Surface Stem (Model 392052):**
High temperature range: -58 to 572°F (-50 to 300°C)
- **Penetration Stem (Model 392050):**
Temperature range: -58 to 302°F (-50 to 150°C)
- Basic Accuracy of 2°F or 1°C
- 0.1° resolution to 199.9; 1° over 200°
- ON/OFF switch saves battery life
- Auto power off after 1hr of non use
- Dimensions: 5" (130mm) stainless steel probe with 2" (54mm) dial
- Weight: 1oz (29g); 1.3oz (30g) with protective sheath
- Includes 1.5V button battery, and plastic protective sheath with pocket clip for model 392050



Stem thermometer ideal for measuring temperature in HVAC applications such as air ducts, vents, and heaters.

Flat surface stem thermometer ideal for measuring high temperature on motors and other flat surface areas including grills.

Ordering Information:

392050Dial Stem Thermometer
392052Dial Flat Surface Stem Thermometer

Distributed by:



TESTERS AND TOOLS.COM

Trust Experience Reliability

sales@testersandtools.com

Tel: 602-795-4033, Fax: 602-795-4624

