

## AN340 CMM/CFM Anemometer/ Psychrometer Datalogger



**Telescoping probe with 18mm diameter vane sensor easily fits into air vents and can extend length of probe to 3.3ft (1m) long. Measures Air Velocity/Volume, Temperature, Humidity, Wet Bulb, and Dew Point. User can store up to 12,000 readings for data analysis.**

**Applications:**

- HVAC with small ducts and vents
- Manufacturing
- Engineering
- Appliance Testing
- Research and Design
- and more!



### Features

- Telescoping 0.7" (18mm) diameter vane sensor extends from 1ft (0.3m) up to 3.3ft (1m)
- Measures Air Velocity, Air Flow, Air Temperature, Humidity, Dew Point and Wet Bulb
- Manually store/recall up to 99 readings
- Automatically datalog up to 12000 readings with 12/24 hour time and date stamp
- Select data sampling rate from 1s to 4hr: 59 min: 59s
- Min/Max/Avg readings
- Data hold and Auto power off with disable
- Built-in PC Interface
- Complete with external mini vane probe, Windows<sup>®</sup> compatible software, USB cable, 6 AAA batteries, and hard carrying case

| Specifications    | Range                                       | Basic Accuracy |
|-------------------|---|----------------|
| m/s               | 0.5 to 20m/s                                | ±3%            |
| ft/min            | 100 to 3940ft/min                           | ±3%            |
| Temperature       | -4 to 140°F (-20 to 60°C)                   | ±1.1°F (0.6°C) |
| Humidity          | 0.1 to 99.9%RH                              | ±3%RH          |
| Wet Bulb          | -4 to 140°F (-20 to 60°C)                   |                |
| Dew Point         | -4 to 140°F (-20 to 60°C)                   |                |
| CFM/CMM           | 0 to 99999                                  |                |
| Dimensions/Weight | 6.7x3x1.7" (169x78.3x44.4mm) / 7.4oz (210g) |                |

### Ordering

AN340..... Mini Vane CFM/CMM Anemometer/Psychrometer Datalogger

**Distributed by:**  
 **TESTERS AND TOOLS.COM**  
 Trust Experience Reliability  
 sales@testersandtools.com  
 Tel: 602-795-4033, Fax: 602-795-4624

