

Gen-Eye Specifications

	Gen-Eye SD™	Gen-Eye Vista™	Gen-Eye POD™	Gen-Eye Micro-Scope™
Line Capacity				
Standard Reel	3" to 10"	3" to 10"	3" to 10"	
Mini-Reel	2" to 4"	2" to 4"	2" to 4"	
Micro-Reel				1-1/2" to 3"
Reel Capacity				
Standard	200, 300, or 400 ft.	200, 300, or 400 ft.	200 ft.	
Mini	100 ft. or 200 ft.	100 ft. or 200 ft.	125 or 175 ft.	
Micro				33 ft. or 100 ft.
Probe-Rod				3 ft.
Rod Size				
Standard	.475" Gel-Rod®	.475" Gel-Rod®	.475" Gel-Rod®	
Mini	.400" Gel-Rod®	.400" Gel-Rod®	.400" Push-Rod	
Micro				.200" Push-Rod
Probe-Rod				.400" Probe-Rod
Camera Dimensions	1.375" x 2.312" L	1.375" x 1.85" L	1" x 1.8" L	1" x 1.38" L – Push-Rod .425" x 1.15" L – Probe-Rod
Sensitivity	.5 Lux	.5 Lux	.5 Lux	.5 Lux
Lighting	16 White LED's	16 White LED's	8 White LED's	12 White LED's Push-Rod 6 White LED's Probe-Rod
White Balance	Auto High Speed	Auto High Speed	Auto High Speed	Auto High Speed
Reel Dimensions	29" L (74 cm) 16" W (41 cm) 33-1/2" H (85 cm)	29" L (74 cm) 16" W (41 cm) 33-1/2" H (85 cm)	18" L (46 cm) 10" W (25 cm) 22" H (56 cm)	17" L (43 cm) 16-1/2" W (42 cm) 7-1/2" H (19 cm)
LCD Monitor Size	8"	8"	7"	3.5"
Command Module Dimensions	10-1/2" L (27 cm) 14" W (36 cm) 6" H (15 cm) (Closed) 12-1/2" H (32 cm) (Open)	21" L (53 cm) 18" W (46 cm) 7-3/4" H (20 cm) (Closed) 20" H (51 cm) (Open)	N/A N/A N/A	10-1/4" L (26 cm) 5-1/4" L (13 cm) 1-7/8" L (4.75 cm)
Command Module Weight	10 lbs. 4.5 kg	24 lbs. 12.8 kg	N/A	1.5 lbs. .7 kg
Audio	Microphone and Speaker	Microphone and Speaker	None	Microphone and Speaker
Video Format	NTSC or PAL	NTSC or PAL	NTSC or PAL	NTSC or PAL
Recording Device	SD Card	SD Card & DVDR	External Connection	SD Card
Power Source	110v/60Hz AC 12v DC	110v/60Hz AC 12v DC	110v/60Hz AC 15v DC	110v/60Hz AC 5v DC
		4 hr. Rechargeable Battery		4 hr. Rechargeable Battery
Operating Temperature	14°F to 122°F (-10°C to 50°C)	14°F to 122°F (-10°C to 50°C)	14°F to 122°F (-10°C to 50°C)	14°F to 122°F (-10°C to 50°C)

General / **General Wire Spring Co.**
PIPE CLEANERS
 McKees Rocks, PA 15136 USA
 412-771-6300 Fax: 412-771-2771
 Web Site: www.drainbrain.com

www.drainbrain.com

MADE IN USA

Distributed by:
TESTERS AND TOOLS.COM
 Trust Experience Reliability
sales@testersandtools.com
 Tel: 602-795-4033, Fax: 602-795-4624