



GREENLEE.
A Textron Company

MADE FOR THE TRADE!™



TESTER, VDV NETcat (POP)

NETcat Micro Digital Voice Data and Video Wiring Tester

Cat No: 52024541

UPC No: 783310236368

Description

- Tests shielded twisted pair (STP), unshielded twisted pair (UTP) and coaxial cables
- TIA/EIA standard wiring pair verification
- Detects shorts, opens, reversed polarity, crossed and split pairs
- Generates three distinct, selectable digital tone patterns for cable tracing and troubleshooting
- Tracing modes can be adjusted for high performance LAN cables
- Complete set of connector types standard (telephone, LAN and coax)
- Nested remote allows end-to-end testing of all wiring types
- Simple testing of LAN wiring and phone lines
- Detection of common wiring and connector errors
- Warning of hazardous voltages
- Checks for reversed telephone wires

Distributed by:



TESTERSANDTOOLS.COM
Trust Experience Reliability

sales@testersandtools.com

Tel: 602-795-4033, Fax: 602-795-4624

Specifications

- Backlight : Green LED
- Battery : 9 V Alkaline Battery (PP3)
- Buttons : Four Momentary Contact Push Button
- Depth : 33.000 MM
- Display LCD : Icon And Seven Segment Type
- Frequency Rating : 577 HZ And 983 HZ
- Humidity : 0 To 95 PCT Non-Condensing
- Interface Connections : RJ45 Shielded Socket, RJ12 6-Way Socket, F-Type Threaded Female Coaxial Connectors
- Length : 150.000 MM
- Minimum Cable Length : 2.000 To 3.000 MR (5.000 To 10.000 FT)
- Pair Tracing Tones : Alternating Frequencies Of 577 HZ And 983 HZ Are Produced At Three User Selectable Rates
- Standard : TIA/EIA
- Storage/Operating Temperature : -10 To 60 DEG C0 - 50 DEG C
- Sub Brand : NETcat
- Type : Micro Digital Voice Data And Video Wiring
- Weight : 220.000 GM Including Remote Unit And Battery
- Width : 70.000 MM