

PRODUCT OVERVIEW

The TECHLITE™ PX-D402 test sets allow technicians to perform precise optical measurements in the field. When operated in absolute power mode, the PX-B240 meter is used to determine the level of optical power being emitted from a transmitter. In relative mode, it is used with the included source to perform fiber loss measurements or splice tuning operations.

TECHLITE™ meters and sources were designed to be rugged. As with all Photonix test instruments, the internal circuitry is housed within an aluminum extrusion with high impact rubber bumpers. In addition, the instruction guide is fully laminated to make it weather-resistant and virtually tear-proof.

The TECHLITE™ meter, in relative measurement mode, will store the zero reference reading for all four wavelengths independently in non-volatile memory. This allows all zero references to be taken at one time and also allows the unit to be turned off while moving between locations preserve battery life. Also in relative mode, the meters will also display a 1dB analog type deviation pointer and an mini-display for real time splice tuning. The TECHLITE™ meters utilize a graphic LCD screen to create unusually large and easy to read numbers as graphics to indicate power levels.

The included TECHLITE™ PX-C202 LED source offers advanced temperature and coupling stability to provide superior test accuracy. The PX-C202 also offers the ability to operate one or both outputs simultaneously in either CW, 30Hz, 500Hz, or 2kHz modulation for use with leak detectors or fiber identifiers.

The units are powered by either four AA alkaline batteries or an AC wall pack with four AA NiMH cells (both the wall pack and NiMH cells are included). In addition to standard charge mode, the units feature an emergency quick charge mode that allows the user to charge the batteries in approximately 4 hours.



PX-B240



PX-C202

Note: Photos may vary from actual product

FEATURES

- Meter: 850nm / 1300nm
- LED Source: 850nm/1300nm
- ST, SC, or FC adapters
- Crush resistant aluminum bodies
- 0.01 dB Meter resolution
- Interchangeable meter adapters
- Built in quick charger
- Sealed waterproof carry case
- Two year warranty



MADE IN USA

Distributed by:



TESTERS AND TOOLS.COM

Trust Experience Reliability

sales@testersandtools.com

Tel: 602-795-4033, Fax: 602-795-4624

SPECIFICATIONS

POWER METER PX-B240

Parameter	Value
Detector	Germanium
Wavelength	850,1300,1310,1550nm
Power Range(1300-1550nm)	+3 to -60dBm
Power Rance(850nm)	+8 to -55dBm
Resolution	0.01dB
Accuracy	+/-0.25dB
Display	dB,dBm
Backlight	Variable
Auto Power Off	Variable
Storage Points	999 per wavelength

LED SOURCE PX-C202

Parameter	Value
Emitter	LED
Wavelength	850,1300nm
Pout	-17dBm (62.5/125)
Stability(8hr)	+/-0.05/.08dB
Bandwidth (typ)	50/170nm
Modulation	30Hz,500Hz,2kHz

ALL PRODUCTS

Parameter	Value
Operating Temp	-5°C to 45°C
Storage Temp	-10°C to 60°C
Humidity	10% to 90% non-cond.
Line Power	110/220VAC, 50-60Hz
Battery Power	US 120VAC 60Hz(inc), NiMH 4-AA(inc), or Alkaline
Battery Life	10 Hours(typ)
Charge Time	12-14 Hours(typ)

Distributed by:



TESTERS AND TOOLS.COM

Trust Experience Reliability

sales@testersandtools.com

Tel: 602-795-4033, Fax: 602-795-4624