



## Micromanometers



Model AXD620

### Micromanometer Models AXD610 and AXD620

The AXD610 is an easy to use, handheld digital Micromanometer for fast, accurate and reliable pressure measurement. It can also calculate velocity.

The AXD620 is a rugged, compact, comprehensive Micromanometer that measures pressure, and calculates velocity and volumetric flow rate. It can be used with Pitot tubes to measure velocity and then calculate flow rates with user-input duct size and shape. Premium features make it ideal for HVAC, environmental safeguards, commissioning, process control and system balancing.

### Features and Benefits

- Measure differential and static pressure from -15 to +15 in. H<sub>2</sub>O (-3735 to +3735 Pa)
- Calculate and display velocity when using a Pitot tube

### Added Features AXD620

- Calculates volumetric flow rate in duct from velocity and user-input duct size and shape
- Records data points in duct traverse using sampling function
- Data logging with time and date stamp
- Includes LogDat2™ downloading software
- Programmable K factors

### Applications

- HVAC commissioning and troubleshooting
- Testing and balancing
- Pitot tube duct traverses
- Static pressure measurements
- Differential pressure measurements

*Rugged. Reliable. Professional.*



### Specifications

Models AXD610 and AXD620

#### Static/Differential Pressure

**Range<sup>1</sup>** -15 to +15 in. H<sub>2</sub>O (-28.0 to +28.0 mm Hg, -3735 to +3735 Pa)

**Accuracy** ±1% of reading ±0.005 in. H<sub>2</sub>O (±1 Pa, ±0.01 mm Hg)

**Resolution** 0.001 in. H<sub>2</sub>O (0.1 Pa, 0.01 mm Hg)

#### Velocity From a Pitot Tube

**Range<sup>2</sup>** 250 to 15,500 ft/min (1.27 to 78.7 m/s)

**Accuracy<sup>3</sup>** ±1.5% at 2,000 ft/min (10.16 m/s)

**Resolution** 1 ft/min (0.1 m/s)

#### Duct Size (AXD620)

**Dimensions** 1 to 250 inches in increments of 0.1 in. (1 to 635 cm in increments of 0.1 cm)

#### Volumetric Flow Rate (AXD620)

**Range** Actual range is a function of velocity, pressure, duct size, and K factor

#### Instrument Temperature Range

**Operating** 40 to 113°F (5 to 45°C)

**Storage** -4 to 140°F (-20 to 60°C)

#### Data Storage Capabilities (AXD620 only)

**Range** 12,700+ samples and 100 test IDs

#### Logging Interval (AXD620 only)

1 second to 1 hour

#### Time Constant (AXD620 only)

User selectable

#### External Meter Dimensions

3.3 in x 7.0 in x 1.8 in (8.4 cm x 17.8 cm x 4.4 cm)

#### Meter Weight with Batteries

0.6 lbs. (0.27 kg)

#### Power Requirements

**AXD620** Four AA-size batteries or optional AC adapter

**AXD610** Four AA-size batteries

	AXD610	AXD620
Differential and static pressure	•	•
Velocity with pitot tube	•	•
Sample statistics		•
Volumetric flow rate		•
Actual and standard velocity		•
Variable time constant		•
LogDat2 downloading software		•
K factor		•
Certificate of Calibration	•	•

<sup>1</sup> Overpressure range = 190 in. H<sub>2</sub>O (7 psi, 360 mmHg, 48 kPa).

<sup>2</sup> Pressure velocity measurements are not recommended below 1000 ft/min (5 m/s).

<sup>3</sup> Accuracy is a function of converting pressure to velocity. Conversion accuracy improves when actual pressure values increase.

Specifications subject to change without notice.



**Value Testers**  
Value Priced Electronic Testers

Tel: (602) 795 - 8292  
Fax: (602) 795 - 4624  
www.valuetesters.com  
sales@valuetesters.com

