

# AC Current Probe Model MN373



The Model MN373 is the latest in compact AC current probes. It is designed to meet the most stringent demands in industry and electrical contracting. Model MN373 meets EN 61010, 600V, Cat. III safety standards and is CE Marked and UL approved for Canada and United States.

The Model MN373 has a 0.78" (20mm) jaw opening and accommodate conductors up to 250MCM. The unique hooked jaw design facilitates clamping and hooking onto conductors. Polycarbonate materials and ultrasonic welding are used throughout to ensure ruggedness and overall lasting reliability.

The Model MN373 is a high performance model and uses a custom nickel core to improve accuracy and phase shift on the low end of the measurement range. The Model MN373 is an excellent probe to be used in power and low level current measurement applications.

## Features

- Small, compact size
- Measurement range of 0.01 to 150A
- Large jaw opening accommodates conductors up to 250MCM
- Designed for DMMs, loggers, recorders and oscilloscopes
- 40Hz to 10kHz response
- 1000mV/AAC – 10mV/AAC output signals
- Designed to EN 61010, 600V, Cat. III safety standard
- UL approved for Canada and United States
- Double Insulation
- CE Mark


## Applications

- Measuring in breaker panels
- Industrial loads
- HVAC
- Residential and commercial sites
- 5A secondary current transformers (CTs) monitoring
- Data logging/recording

# Specifications

MODEL	MN373
<b>ELECTRICAL</b>	
Nominal Range	2A & 150A
Measurement Range	0.1 to 150A
Transformation Ratio	Voltage output
Output Signal	2A: 1000mV/A; 150A: 10mV/A
Accuracy (2A Range)	
0.01 to 0.1A	5% of Reading $\pm$ 2mV
0.1 to 1A	3% of Reading $\pm$ 1mV
1 to 2.4A	1% of Reading
Phase Shift (2A Range)	Not Specified
Overload (2A Range)	2.4A for 10 min ON & 30 min OFF
Accuracy (150A Range)	
0.1 to 1A	3% of Reading $\pm$ 200 $\mu$ V
1 to 20A	2% of Reading $\pm$ 200 $\mu$ V
20 to 80A	1% of Reading
80 to 150A	3% of Reading
150 to 200A	Not Specified
Phase Shift (150A Range)	
0.1 to 1A	Not Specified
1 to 20A	$\leq 3^\circ$
20 to 80A	$\leq 2^\circ$
80 to 150A	$\leq 3^\circ$
150 to 200A	$\leq 4^\circ$
Overload	240A for 10 min ON, 30 min OFF
Frequency Range	40 to 10kHz
Limit Operating	200A permanently to 1kHz; Derating above 3kHz: 200A x (1/0.333F), F in kHz to 1kHz
Crest Factor	2A: 5 @ 4A Peak with an error (due to CF) of 5% 200A: 5 @ 480A Peak with an error (due to CF) of 5%
Working/Common Mode Voltage	600Vrms
Output Termination	5 ft Lead
<b>MECHANICAL</b>	
Operating Temperature	14° to 131°F (-10° to 55°C)
Storage Temperature	-40° to 158°F (-40° to 70°C)
Operating Relative Humidity	10 to 35°C 85% RH (without roll-off above 35°C)
Jaw Opening	0.83" (21mm)
Maximum Conductor Size	0.78" (20mm)
Dimensions	5.47 x 2.00 x 1.18" (139 x 51 x 30mm)
Weight	6.5 oz (180g)
Polycarbonate Material	Polycarbonate with fiberglass charge, UL94 V0
<b>SAFETY</b>	
Electrical	EN 61010-2-32
UL Approval	Yes – Canada and United States
Double Insulation <input type="checkbox"/>	Yes
CE Mark	Yes

Note: Reference conditions: 20 to 26°C, 20 to 75% RH, external magnetic field <40A/m, 48 to 65Hz sine wave, distortion factor less than 1%, no DC component, no external current carrying conductor, test sample centered. Load impedance > 1 $\Omega$



**Leads:**  
 Double/reinforced  
 5 ft (1.5m) lead  
 with safety 4mm  
 banana plug

**ORDERING INFORMATION**

**CATALOG NO.**

**AC Current Probe Model MN373** (Lead – 1000mA/A – 2.4A max & 10mV/A 150A max)..... **Cat. #2116.28**

Includes a user manual

**Accessories (Optional)**

Banana plug adaptor (Safety Leads to nonrecessed plug)..... **Cat. #1017.45**

Banana (Female) – BNC (Male) Adaptor..... **Cat. #2118.46**

## Contact Us

### United States and Canada:

Chauvin Arnoux<sup>®</sup>, Inc.  
d.b.a. AEMC<sup>®</sup> Instruments  
200 Foxborough Blvd.  
Foxborough, MA 02035 USA  
(508) 698-2115 • Fax (508) 698-2118  
[www.aemc.com](http://www.aemc.com)

**Customer Support – for placing an order, obtaining price and delivery:**  
[customerservice@aemc.com](mailto:customerservice@aemc.com)

**Sales Department – for general sales information:**  
[sales@aemc.com](mailto:sales@aemc.com)

**Repair and Calibration Service – for information on repair and calibration, obtaining a user manual:**  
[repair@aemc.com](mailto:repair@aemc.com)

**Technical and Product Application Support – for technical and application support:**  
[techinfo@aemc.com](mailto:techinfo@aemc.com)

**Webmaster – for information regarding [www.aemc.com](http://www.aemc.com):**  
[webmaster@aemc.com](mailto:webmaster@aemc.com)

### South America, Central America, Mexico, Caribbean, Australia and New Zealand:

Chauvin Arnoux<sup>®</sup>, Inc.  
d.b.a. AEMC<sup>®</sup> Instruments  
15 Faraday Drive  
Dover, NH 03820 USA  
(978) 526-7667 • Fax (978) 526-7605  
[export@aemc.com](mailto:export@aemc.com)  
[www.aemc.com](http://www.aemc.com)

### All other countries:

Chauvin Arnoux SCA  
190, rue Championnet  
75876 Paris Cedex 18, France  
33 1 44 85 45 28 • Fax 33 1 46 27 73 89  
[info@chauvin-arnoux.com](mailto:info@chauvin-arnoux.com)  
[www.chauvin-arnoux.com](http://www.chauvin-arnoux.com)



**Value Testers**  
*Value Priced Electronic Testers*

Tel: (602) 795 - 8292  
Fax: (602) 795 - 4624  
[www.valuetesters.com](http://www.valuetesters.com)  
[sales@valuetesters.com](mailto:sales@valuetesters.com)