708
Data Sheet
02.11

708 Combustion Analyzer

Test the TPI Advantage

Features

QUICK AND SIMPLE SET UP All TPI analyzers feature quick and simple set up. Fast purge and the ability to perform fuel selectionduring start up enable tests to be performed quickly without requiring extra set-up time after initial startup. TPI analyzers also use the last selected fuel as the default setting. This feature prevents the need toperform fuel selection every time the analyzer is turned on.

- Calculates combustion efficiency
- Pump driven for fast response
- Will not shut off if 15 ppm CO is present for increased safety
- Ten selectable fuels
- Optional A740 IR printer available for hard copies of test results
- Built-in differential thermometer
- Store function to save up to 50 readings
- Store function to save up to 50 readings
- Large easy to read backlit display

www.tpi-thevalueleader.com

Specifications

Instrument

Operating Temperature Range	14°F to +122°F (-10°C to +50°C)
Battery / Batery Life	AA (3) / > 6 Hours
Fuels	Natural Gas, LPG, Light Oil, Heavy Oil, Bituminous Coal, Anthracite Coal, Coke, Butane, Wood, Bagasse
Display	3 Line Backlit LCD w/ annunciators
Data Storage	50 sets of readings
Time & Date	24 Hour Real Time Clock
Dimensions	7.8” x 3.5” x 2.4”
Weight	1.1lbs

Distributed by:
TESTERS AND TOOLS.COM
Trust Experience Reliability
sales@testersandtools.com
Tel: 602-795-4033, Fax: 602-795-4624

Gases	Range	Resolution	Accuracy
Oxygen	0-25%	0.1%	+/- 0.3%
Carbon Monoxide	0-10,000 ppm	1 ppm	+/- 5 ppm or 5%
Carbon Dioxide	0-25%	0.1%	Calculated
CO/CO2 Ratio	0-0.999	0.001	Calculated
Combustion Eff.	0-100%	0.1%	Calculated

Temperature Measurement

Input Type	K-Type thermocouple
Range	-58°F to 1832°F (-50°C to 1000°C)
Resolution	1°F (1°C)
Accuracy	+/- (0.3% of rdg + 2°F) or +/- (0.3% of rdg + 1°C)

A787 Soft Carrying Case

GK11M K-type thermocouple

A763 Mini pump protection filter

A770 Flue Probe

Copyright © 2010 Test Products International, Inc.