

eL-320

# Combustible Gas Leak Detector

**The AccuTools® eL-320 Combustible Gas Leak Detector is the most technologically advanced of its kind.**

The fully automatic eL-320's low power requirements, small size and high sensitivity combine to create a tool which is easy to handle and ultra effective at locating even the most difficult-to-find leaks.

The eL-320's long life sensor will detect concentrations of combustible gases as low as 5 ppm. It is sensitive to all combustible gases.

## Features

- Lightweight, ergonomic design
- Simple, one button operation
- Two sensitivity modes, enabling quick and easy location of large and small leaks
- Sturdy blow-molded carrying case
- Both visual and audible leak detection signal
- Low battery indicator
- Automatic power-off to conserve battery life
- Extra sensor storage

Dimensions	7.25" x 2.25" x 1.5" (19 cm x 5.7 cm x 3.8 cm)
Weight	7 oz (190 g)
Batteries	2 x 1.5V 'AA' Alkaline Batteries (3 VDC)
Battery Life	11 Hours
Sensitivity	Less Than 50 ppm (propane, iso-butane, methane)
Sensor Lifetime	>1 Year Normal Use
Operating Temperature	32 - 122°F (0 - 50°C)
Warm-up Time	25 Seconds - 1.5 Minutes
Calibration	Auto
Response Time	5 Seconds
Reset Time	5 Seconds or More Depending on Gas Concentration
Probe Length	12" (30 cm)



Classified by Underwriters Laboratories, Inc. Only as to fire, electrical shock, and explosion hazards in class I, division 2 groups A, B, C, & D hazardous locations. Read owners manual before operating. Use only 1.5V 'AA' alkaline batteries.

Distributed by:  
 **TESTERSANDTOOLS.COM**  
Trust Experience Reliability  
sales@testersandtools.com  
Tel: 602-795-4033, Fax: 602-795-4624



3650 Coral Ridge Drive, Suite 101 • Coral Springs, FL 33065  
954.227.0781 • Fax 954.227.1094 • AccuTools.com

©2018 AccuTools. All Rights Reserved.

